

Elvex Quattro™ Ear Plugs

Quattro is a universal size reusable ear plug, designed to be used over and over again, with maintained comfort and effectiveness. Elvex Quattro offers the following features:

- A four flange design that allows this ear plug to fit almost all ear canals.
- An ultra-soft polymer provides a comfortable and effective seal.
- A sturdy and stiff handle that allows an easy grip for insertion and removal.
- Material is resistant to ear wax and body oils, and will outlast PVC ear plugs by many months.
- Polymer is non-allergenic and non-irritating to the sensitive skin in the ear canal.
- Noise Reduction Rating is 25 dB, and the test was performed to ANSI S3.19-1974 at an independent and certified laboratory, NVLAP #0427.
- Quattro has been assigned U.S. Military national stock numbers.



EP-401

Packaging Alternatives

Elvex Quattro is available in six different versions.

- EP-401** Standard Quattro ear plugs packaged in individual poly-bags. 100 per dispenser box, 4 boxes per carton.
- EP-411** Corded Quattro ear plugs packaged in individual poly-bags. 100 per dispenser box, 4 boxes per carton.
- EP-413** PVC-Corded Quattro packaged in individual poly-bags. 100 per dispenser box, 4 boxes per carton.
- EP-402** Standard Quattro ear plugs, with plastic case and chain, packaged in individual poly-bags. 50 units per box, 4 boxes per carton.
- EP-412** Corded Quattro ear plugs, with plastic case and chain, packaged in individual poly-bags. 50 units per box and 4 boxes per carton.
- EP-415** Metal detectable, corded Quattro ear plugs in individual poly-bags. 100 per box, 4 boxes per carton.

CE



NRR=25 dB

SNR=26 dB



ANSI S3-19-1974	Frequency, Hz	125	250	500	1000	2000	3150	4000	6300	8000	H	M	L	NRR
	Mean Value, dB	29.4	30.8	31.8	32.1	33.1	37.8	36.8	39.5	39.5	32	29	28	25
	Std. Deviation	4.3	4.0	3.9	3.3	2.6	3.6	3.3	4.5	2.8				

CE EN-352-2:1993	Frequency, Hz	63	125	250	500	1000	2000	4000	8000	H	M	L	SRR
	Mean Value, dB	25.1	26.8	25.7	26.5	25.2	32.9	33.9	39.4				
	Std. Deviation	5.7	4.7	5.7	5.7	4.2	4.8	5.2	6.7	27	22	21	26
Protection Value	19.4	22.1	20.0	20.8	21.0	28.1	28.7	32.7					